

Index

1	Introduction	1
1.1	Energy demand and contribution of natural gas to the energy mix	1
1.2	Power generation with natural gas	2
1.3	Gas Turbines	3
2	TBC Systems	5
2.1	Turbine blade superalloy (substrate)	6
2.2	Bond Coat	7
2.3	Thermal barrier coating (TBC)	14
3	Oxidation of MCrAlY-coatings	17
3.1	Oxidation Reaction	17
3.2	Formation of the thermally grown oxide (TGO) in TBC systems	20
3.3	Failure mechanisms of coating systems	24
4	Purpose of this investigation	28
5	Experimental Procedure	30
RESULTS AND DISCUSSION		35
6	Effect of the Bond Coat chemical composition on the oxide growth and adherence	35
6.1	Oxidation studies on TBC systems with MCrAlY-coatings	35
6.1.1	Lifetime of TBC systems	35
6.1.2	TGO stress measurements in TBC systems	36
6.1.3	TGO growth and morphology in TBC systems	37
6.2	Oxidation studies on overlay MCrAlY coatings	39
6.2.1	TGO growth and morphology in overlay coatings with as- spayed surfaces	39
6.2.2	Exposure of overlay coatings with ground surfaces	40
6.3	Oxidation studies on free-standing MCrAlY-coatings	44
6.3.1	TGO growth and morphology after discontinuous exposure	44
6.3.2	Characterization of Y/Al-oxide compounds	45
6.3.3	Oxidation kinetics of free-standing MCrAlY-coatings during isothermal exposure	49
6.3.4	Oxidation kinetics and scale adherence on MCrAlY-coatings during cyclic exposure	57

6.4 Summary and final comments	59
7 Temperature dependence of phase relationships in different MCrAlY-coatings	61
7.1 General remarks	61
7.2 Modeling of phase equilibria in commercial MCrAlY-coatings	62
7.2.1 Modelling of phase equilibria in NiCoCrAlY(hi-Al)	62
7.2.2 Modelling of phase equilibria in NiCoCrAlY(lo-Al)	63
7.2.3 Modelling of phase equilibria in CoNiCrAlY	63
7.3 Microstructure of annealed MCrAlYs in the temperature range 800-1100°C	64
7.3.1 Microstructure at 1100°C	64
7.3.2 Microstructure at 1000°C	66
7.3.3 Microstructure at 900°C	67
7.3.4 Microstructure at 800°C	68
7.4 Physical CTE measurements on free-standing MCrAlYs	70
7.5 Accuracy of thermodynamic calculations	71
7.5.1 Accuracy of phase composition calculations	71
7.5.2 Accuracy of volume fraction calculations	72
7.6 Correlation of experimental findings with observations in a gas turbine blade after service	74
7.7 Summary	78
8 Geometrical effects on the oxide growth and morphology in MCrAlY-coatings	80
8.1 General Remarks	80
8.2 Effect of coating roughness	81
8.2.1 TGO growth and morphology on rough surfaces	81
8.2.2 Temperature dependence of the effect of roughness	86
8.2.3 Characterization of Y-rich compounds	86
8.2.4 Mechanistic explanation of the effect of roughness	88
8.2.5 Limitations of the effect of roughness	89
8.3 Effect of coating thickness	92
8.3.1 General remarks	92
8.3.2 Effect of coating thickness during discontinuous oxidation	92
8.3.3 Effect of coating thickness during cyclic oxidation	96
8.3.4 Discussion on the effect of Y-reservoir on the TGO growth rate and adherence	101
8.4 Summary on the geometrical effects	102

9	Effect of pre-treatment and processing on the oxidation behavior of MCrAlY-coatings	104
9.1	General remarks	104
9.2	Effect of surface processing sequence (Heat treated vs. heat treated and ground)	105
9.2.1	Modifications of the surface chemical composition by vacuum heat treatment	105
9.2.2	Discontinuous exposure of MCrAlYs with different initial surface Condition	108
9.2.3	Cyclic exposure of MCrAlYs with different initial surface condition (HT vs. HT+G)	116
9.2.4	Mechanism of the effect of the initial surface condition on the MCrAlY oxidation	122
9.3	Effect of heat treatment conditions	126
9.3.1	General remarks	126
9.3.2	Alteration of the surface chemical composition by alternative heat treatments	127
9.3.3	Discontinuous exposure of MCrAlYs subjected to alternative heat treatments	128
9.4	Effect of oxygen impurities on the oxidation behavior of VPS MCrAlY-coatings	134
9.4.1	General remarks	134
9.4.2	Isothermal oxidation of free-standing MCrAlYs with varying O-content	135
9.4.3	Estimation of amount of Y bound in MCrAlYs with varying O-content	140
9.5	Summary on the effect of pre-treatment	142
10	Effect of the TGO growth rate on the lifetime of TBC systems	144
10.1	General Remarks	144
10.2	Lifetime of EB-PVD-coated specimens in air and Ar- 4% H ₂ - 2% H ₂ O environments at 1100°C	145
10.3	Lifetime of APS-coated specimens in Air + 2% H ₂ O and Ar- 4% H ₂ - 2% H ₂ O environments at 1100°C	149
10.4	Summary and final comments	153
11	Summary and Conclusions	154
12	References	158