



Lattice Boltzmann Simulation in Components of Polymer Electrolyte Fuel Cell

Junliang Yu

Energie & Umwelt / Energy & Environment

Band / Volume 438

ISBN 978-3-95806-360-0

Forschungszentrum Jülich GmbH
Institut für Energie- und Klimaforschung
Elektrochemische Verfahrenstechnik (IEK-3)

Lattice Boltzmann Simulation in Components of Polymer Electrolyte Fuel Cell

Junliang Yu

Schriften des Forschungszentrums Jülich
Reihe Energie & Umwelt / Energy & Environment

Band / Volume 438

ISSN 1866-1793

ISBN 978-3-95806-360-0

Contents

| | | |
|----------|--|-----------|
| 1 | Introduction and literature review | 1 |
| 1.1 | Motivation and goal | 3 |
| 1.2 | Two-phase flow in GDL of PEFC | 4 |
| 1.2.1 | Two-phase flow mechanisms | 5 |
| 1.2.2 | Two-phase flow simulations and experiments | 8 |
| 2 | Methods | 11 |
| 2.1 | ShanChen MCMP model | 12 |
| 2.1.1 | ShanChen MCMP model with SRT approach | 13 |
| 2.1.2 | ShanChen MCMP model with MRT approach | 15 |
| 2.2 | Force schemes in ShanChen MCMP model | 16 |
| 2.3 | Open boundary condition | 18 |
| 2.4 | Unit conversion | 19 |
| 2.5 | Apparent contact angle on rough surface | 21 |
| 3 | Simulation framework | 25 |
| 3.1 | Simulation process | 25 |
| 3.2 | Geometry introduction | 27 |
| 4 | Model validation | 31 |
| 4.1 | External force driving Poiseuille flow test | 31 |
| 4.2 | Flat interface test | 37 |
| 4.2.1 | Steady flat interface test | 37 |
| 4.2.2 | External force driving layered Poiseuille flow | 43 |
| 4.3 | Droplet test | 47 |
| 4.3.1 | Single ideal droplet test | 47 |
| 4.3.2 | Cubic initialization test | 52 |
| 4.3.3 | Coalescence test | 54 |
| 4.4 | Contact angle test | 57 |
| 4.5 | Open boundary condition test | 63 |
| 4.6 | Summary | 67 |
| 5 | Simulation of liquid water through GDL | 69 |
| 5.1 | Simulation setups and conditions | 69 |
| 5.2 | Buffer space thickness effect | 71 |
| 5.3 | Domain size effect | 75 |
| 5.4 | Capillary number effect | 78 |
| 5.5 | Geometry effect | 82 |
| 5.6 | Wettability effect | 91 |
| 5.7 | Summary | 93 |

| | | |
|----------|--|------------|
| 6 | Statistic analysis of liquid water through GDL | 95 |
| 6.1 | Apparent contact angle | 95 |
| 6.2 | Breakthrough point distance | 100 |
| 7 | PTFE effects on water through GDL | 107 |
| 7.1 | Simulation setups and conditions | 107 |
| 7.2 | In-plane PTFE distribution | 110 |
| 7.3 | Whole-GDL PTFE distribution | 115 |
| 7.4 | Two-sections-through-plane PTFE distribution | 117 |
| 7.5 | Sandwich-through-plane PTFE distribution | 121 |
| 7.6 | Quasi-linear-through-plane PTFE distribution | 128 |
| 8 | Discussion | 131 |
| 9 | Conclusion | 135 |
| | References | 137 |
| A | Appendix | 151 |
| A.1 | Transformation matrix in MRT | 151 |
| A.2 | Example of unit conversion | 152 |
| A.3 | SPPF method in MATLAB | 152 |
| B | Abbreviate | 155 |
| B.1 | Acronyms | 155 |
| B.2 | Latin symbols | 159 |
| | List of Figures | 165 |
| | List of Tables | 171 |
| C | Acknowledgments | 173 |

Energie & Umwelt / Energy & Environment
Band / Volume 438
ISBN 978-3-95806-360-0

Mitglied der Helmholtz-Gemeinschaft

