



## Future Grid Load of the Residential Building Sector

Leander Kotzur

Energie & Umwelt / Energy & Environment

Band / Volume 442

ISBN 978-3-95806-370-9

Forschungszentrum Jülich GmbH  
Institut für Energie- und Klimaforschung  
Elektrochemische Verfahrenstechnik (IEK-3)

# **Future Grid Load of the Residential Building Sector**

Leander Kotzur

Schriften des Forschungszentrums Jülich  
Reihe Energie & Umwelt / Energy & Environment

Band / Volume 442

---

ISSN 1866-1793

ISBN 978-3-95806-370-9

---

# Contents

<b>Abstract</b>	<b>i</b>
<b>Überblick</b>	<b>iii</b>
<b>Acknowledgement</b>	<b>v</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Motivation and objective . . . . .	1
1.2 Structure . . . . .	2
<b>2 Related work</b>	<b>5</b>
2.1 Strategies for greenhouse gas emission reduction . . . . .	5
2.2 Grid impact of residential buildings and self-consumption . . . . .	10
2.3 Optimal design of energy supply systems . . . . .	12
2.4 Discussion . . . . .	17
2.5 Summary . . . . .	20
<b>3 Optimal residential energy supply</b>	<b>21</b>
3.1 Residential electricity load . . . . .	21
3.1.1 Existing electricity load models . . . . .	22
3.1.2 Extension of the <i>CREST</i> model . . . . .	25
3.1.3 Validation and parametrization . . . . .	26
3.2 Thermal building load . . . . .	30
3.2.1 Existing thermal building models . . . . .	31
3.2.2 Extension of the 5R1C model . . . . .	33
3.2.3 Validation and parametrization . . . . .	37
3.3 Supply system optimization . . . . .	40
3.3.1 Objective functions . . . . .	41

3.3.2	Technology classes . . . . .	42
3.3.3	Heat supply model . . . . .	44
3.3.4	Photovoltaic performance model . . . . .	49
3.3.5	Solar thermal performance . . . . .	51
3.3.6	Superstructure of the building model . . . . .	52
3.4	Time series aggregation and disaggregation . . . . .	53
3.4.1	Related work to time series aggregation . . . . .	53
3.4.2	Model reformulation . . . . .	54
3.4.3	Time series disaggregation . . . . .	56
3.5	Discussion . . . . .	57
3.6	Summary . . . . .	59
<b>4</b>	<b>Aggregation of an archetype building stock</b>	<b>61</b>
4.1	Existing definitions of building archetypes . . . . .	61
4.2	Relevant building attributes . . . . .	64
4.2.1	General attribute categories . . . . .	64
4.2.2	Considered attributes for the aggregation . . . . .	65
4.3	Aggregation algorithm . . . . .	70
4.3.1	Mathematical problem formulation . . . . .	70
4.3.2	Solving algorithm . . . . .	72
4.4	Validation aggregation algorithm . . . . .	75
4.5	Discussion . . . . .	82
4.5.1	Further building attributes . . . . .	82
4.5.2	Strengths and limitations of the aggregation . . . . .	83
4.6	Summary . . . . .	85
<b>5</b>	<b>Energy supply scenarios for the German residential building stock</b>	<b>87</b>
5.1	Techno-economic assumptions . . . . .	87
5.1.1	Assumptions for 2015 . . . . .	88
5.1.2	Assumptions for 2050 . . . . .	91
5.2	<i>Reference</i> scenario . . . . .	95
5.2.1	Impact of the number of archetype buildings . . . . .	96
5.2.2	Impact of different weather years . . . . .	99
5.2.3	Spatial distribution of energy demand, cost and GHG footprints	102
5.3	<i>Min Cost</i> scenario in 2050 . . . . .	105
5.3.1	Nationwide analysis . . . . .	105

---

5.3.2	Diversity of the energy supply . . . . .	112
5.3.3	Value of analysis . . . . .	119
5.3.4	Sensitivity of the gas price . . . . .	124
5.3.5	Zero GHG emissions . . . . .	126
5.4	Discussion . . . . .	135
5.4.1	Evaluation of the scenario results . . . . .	135
5.4.2	Comparison of the scenario results to the literature . . . . .	137
5.4.3	Discussion of the model approach . . . . .	141
5.5	Summary . . . . .	143
<b>6</b>	<b>Summary</b>	<b>145</b>
6.1	Scope and objective . . . . .	145
6.2	Methodology and contributions . . . . .	146
6.3	Scenario results . . . . .	147
6.4	Conclusions . . . . .	149
	<b>Appendix A Optimal residential energy supply</b>	<b>151</b>
A.1	Electricity load model . . . . .	151
A.1.1	Resident data . . . . .	151
A.1.2	Seasonal fitting of the electricity load model . . . . .	154
A.1.3	Deviation between the electricity load model and the two validation profiles . . . . .	155
A.2	Building parameters . . . . .	156
A.3	Techno-economic parameters . . . . .	159
A.3.1	Photovoltaic . . . . .	160
A.3.2	Battery . . . . .	163
A.3.3	Fuel cell . . . . .	166
A.3.4	Heat pump . . . . .	168
A.3.5	Oil and gas boiler . . . . .	170
A.3.6	Internal combustion engine . . . . .	171
A.3.7	Heat storage . . . . .	172
A.3.8	Solar thermal . . . . .	173
A.3.9	Pellet boiler . . . . .	173
	<b>Appendix B Aggregation of an archetype building stock</b>	<b>175</b>
B.1	Socio-structural changes . . . . .	175
B.2	Aggregated attribute fitting . . . . .	176

B.3	Number of archetypes representing a municipality . . . . .	179
<b>Appendix C</b>	<b>Scenario results for the German residential building stock</b>	<b>181</b>
C.1	Reference scenario . . . . .	181
C.2	Load change predicted with different numbers of archetype buildings	183
C.3	Value of analysis . . . . .	185
C.4	Sensitivity to the gas price . . . . .	188
C.5	Zero GHG . . . . .	191
	<b>Bibliography</b>	<b>193</b>

Energie & Umwelt / Energy & Environment  
Band / Volume 442  
ISBN 978-3-95806-370-9